




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/38	A2	(11) International Publication Number: WO 99/30524 (43) International Publication Date: 17 June 1999 (17.06.99)
<p>(21) International Application Number: PCT/SE98/02254</p> <p>(22) International Filing Date: 8 December 1998 (08.12.98)</p> <p>(30) Priority Data: 19975783 9 December 1997 (09.12.97) NO</p> <p>(71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE).</p> <p>(72) Inventors: MONRAD, Atle; Stemmen 15, N-4820 Froland (NO). GANGSÖY, Ole, Jonny; Baskjaeråsen 1, N-4800 Arendal (NO).</p> <p>(74) Agent: ERICSSON RADIO SYSTEMS AB; Common Patent Dept., S-164 80 Stockholm (SE).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>Without international search report and to be republished upon receipt of that report.</i></p>	

(54) Title: METHOD FOR ROUTING AREA (RA) UPDATE



Periodic SGSN Routing Area Update Procedure

(57) Abstract

The present invention relates to a method for routing area (RA) update request messages which in accordance with a time period broadcasted from the network are periodically sent from an MS (Mobile Station) to an SGSN (Serving GPRS Support Node) through a BSS (Base Station System), which SGSN supports GPRS (General Packet Radio Service), and which as a result of a routing area update procedure will return an appropriate accept message, and for the purpose of taking into account the differentiation in nature of normal routing area update procedure and periodic updates, it is according to the present invention suggested that for the purpose of simplifying said routing area update procedure, there is broadcasted a new indicator from the network together with the time period for the periodic routing updates, said indicator being adapted to determine whether the periodic routing update procedure is performed ciphered instead of unciphered.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

METHOD FOR ROUTING AREA (RA) UPDATEField of the invention

5

The present invention relates to a method for routing area (RA) update request messages which in accordance with a time period broadcasted from an associated network are periodically sent from an MS (Mobile Station) to an SGSN (Serving GPRS Support Node) through a BSS (Base Station System), which SGSN supports GPRS (General Packet Radio Service), and which as a result of a routing area update procedure will return an appropriate accept message.

15

Background of the invention

GPRS (General Packet Radio Service), that is currently being specified by ETSI as a service for GSM phase 2+, provides packet switched connections throughout the PLMN (Public Land Mobile Network). The packet switching is performed between the nodes in the network and on the radio interface.

25 The most critical part of the transmission is between an MS (mobile station) and the SGSN (Serving GPRS Support Node). The unpredictable change of the position of an MS has led to a wish for quite frequent update messages from the MS towards the network. These frequent messages cause
30 a load on both the air interface and internally within the SGSN.

The protocol stack for GPRS between MS and SGSN is sketched in Figure 1.

35

The problem area

For the mobile telephony system to know the position of a mobile station and whether the mobile station really has radio contact with the system, periodic messages from the mobile stations are specified. The time period between the periodic messages is broadcasted from the network towards the mobile stations. With a scenario of 100.000 attached subscribers and 15 minutes updating interval, a considerable number of routing update procedures must be performed every minute. This will consume a significant part of the total processor capacity for the SGSN.

15 Prior art

The current procedure will be discussed in the following:

Routing Area Update Request messages shall be sent unciphered, since in the inter-SGSN routing area update case the new SGSN shall be able to process the request.

20

The intra SGSN routing area update procedure is illustrated in Figure 2. The example assumes that the MSC/VLR is not changed during the routing update. Each step is explained in the list illustrated in Figure 2.

25

- 1) The MS sends a Routing Area Update Request (TLLI, new CI, old RAI, new RAI) to the SGSN. CI is added in the BSS to reduce the load on the radio interface.
- 30 2) Security functions may be executed.
- 3) The SGSN validates the MS's presence in the new RA. If, due to regional, national or international restrictions, the MS is not allowed to attach in the RA or subscription checking fails, then the SGSN rejects the routing update with an appropriate
- 35 cause. If all checks are successful then the SGSN

updates the MM context for the MS. A new TLLI may be allocated. A Routing Area Update Accept (TLLI, Cause) is returned to the MS.

- 4) If TLLI was changed, the MS acknowledges the new TLLI with Routing Area Update Complete(TLLI).
If the routing area update procedure fails a maximum allowable number of times, or if the Routing Area Update Accept Cause parameter indicates a reject, the MS shall enter IDLE state.

Shortcoming of the Prior Art

The working assumption does not take into account the differentiation in nature of the normal routing area update procedure (always in an unknown area) and periodic updates (always in a known area).

Objects of the present invention

An object of the present invention is to provide a method by which the shortcomings of the prior art are eliminated.

Another object of the present invention is to provide a method for routing area update request messages wherein the processor load consumption is reduced.

Still another object of the present method is to take into account the differentiation in nature of the normal routing area update procedure and periodic updates.

Brief summary of the invention

The above objects are achieved in a method as stated in the preamble, which according to the present invention is characterized in that for the purpose of simplifying said routing area update procedure, there is broadcasted a new indicator from the network together with the time periode

for the periodic routing updates, said indicator being adapted to determine whether the periodic routing update procedure is performed ciphered instead of unciphered.

- 5 In other words, it is proposed that a new indicator is broadcasted from the network together with the time period for the periodic routing updates. This indicator determines whether the periodic routing update procedure is performed ciphered instead of unciphered as normally.
- 10 This leads to a new variant of routing area update. It is also possible to add a second information element from the SGSN, to indicate the number of consecutive periodic routing area updates to perform before a routing area update procedure involving security functions is carried
- 15 out.

Further features and advantages of the present invention will appear from the following description taken in conjunction with the enclosed drawings, as well as from the appending patent claims.

20 Brief disclosure of the drawings

Fig. 1 is a sketch illustrating the protocol stack for GPRS between MS and SGSN.

Fig. 2 is a list illustrating a prior art intra SGSN routing area update procedure.

- 25 Fig. 3 is a list illustrating a periodic SGSN routing area update procedure according to the present invention.

Description of embodiments

From the previous description it should be noted that Fig. 1 is a sketch illustrating the protocol stack for GPRS between MS and SGSN, whereas Fig. 2 is a list illustrating the intra SGSN routing area update procedure according to prior art.

With reference to Fig. 3 it will now be given a detailed description of how an embodiment of the method according to the present invention can be carried out.

10 The periodic SGSN routing area update procedure is illustrated in Fig. 3. Each step is explained in the list illustrated therein.

- 1) The MS sends a Routing Area Update Request (TLLI, CI, RAI, periodic RA indicator) to the SGSN. CI is added in the BSS to reduce the load on the radio interface. The MS initiates the periodic routing area update procedure only in case of no change of routing area. The MS may decide to perform e.g. every 5th periodic RA update as a normal RA-update in order to possibly change authentication data.
- 2) The fact that the SGSN recognises the message after deciphering, and that the periodic RA indicator is present, validates the MS's presence in the RA. The SGSN updates the MM context for the MS. A new TLLI may be allocated. A Routing Area Update Accept (TLLI, Cause) is returned to the MS.
- 3) If TLLI was changed, the MS acknowledges the new TLLI with Routing Area Update Complete(TLLI). If the routing area update procedure fails a maximum allowable number of times, or if the Routing Area Update Accept Cause parameter indicates a reject, the MS shall enter IDLE state.

Summary of invention

The proposed solution can be characterised by providing a simpler periodic routing area update procedure. By letting the procedure be ciphered, it is verified that the correct subscriber is addressed.

Merits of the invention

10 The invention makes it possible to have a more efficient handling of periodic update messages, as they occur in a known routing area and thereby can be handled as other information known by both the MS and the SGSN. The information can then e.g. be sent in ciphered form.

15 Further, the method according to the present invention may be defined by sending an indicator to the mobile stations, for thereby being able to handle the periodic routing area update procedures in ciphered or unciphered form according to operator's wishes.

20 Further, the method according to the present invention makes it possible to let the mobile stations, at certain defined intervals, handle the periodic routing area updates as ordinary routing area updates in order to perform security functions.

25 Still further, the present invention defines the principle of letting the periodic routing area update procedure be sent in ciphered or unciphered form.

30

P a t e n t c l a i m s

5 1. Method for routing area (RA) update request messages
which in accordance with a time period broadcasted from
the network are periodically sent from an MS (Mobile Sta-
tion) to a Service Node, and which as a result of a rout-
ing area update procedure will return an appropriate ac-
10 cept message,

 c h a r a c t e r i z e d i n that for the purpose of
simplifying said routing area update procedure, there is
broadcasted a new indicator from the network together
with the time periode for the periodic routing updates,
15 said indicator being adapted to determine whether the pe-
riodic routing update procedure is performed ciphered in-
stead of unciphered.

 2. Method as claimed in claim 1,
20 c h a r a c t e r i z e d i n that there is added a
second information element from said Service Node, which
information element may indicate the number of consecu-
tive periodic routing updates to be performed before a
routing area update prosedure involving security func-
25 tions may be effected.

 3. Method as claimed in claim 1 or 2,
 c h a r a c t e r i z e d i n that the involved MS
initiates the periodic routing area update procedure only
30 in case of no change of routing area.

 4. Method as claimed in claim 3,
 c h a r a c t e r i z e d i n that the involved MS is
adapted to decide to perform only some periodic RA up-
35 dates as a normal RA update, for example every 5th peri-
odic RA update, in order to possibly change authentica-
tion data.

5. Method as claimed in any of the preceding claims, characterized in that when the Service Node recognizes the message after deciphering and the presence of said indicator, then the Service Node will
- 5 validate the presence of the involved MS in the routing area, whereby the MM context of said MS is updated and possibly a new TLLI (Temporary Logic Link Identity) may be allocated.

1/2




Figure 1: GPRS Protocol Stack

2/2




Figure 2:
Intra SGSN Routing Area Update Procedure




Figure 3:
Periodic SGSN Routing Area Update Procedure